

## Product Specifications

<b>Product</b>	Pipemark UV+ INDOOR
<b>Base Material</b>	Gloss white polyethylene film with top coating.
<b>Adhesive</b>	Clear permanent acrylic adhesive.
<b>Backing Paper</b>	51micron white, supercalendered glassine paper.
<b>Face Thickness</b>	80 micron
<b>Dimensions</b>	275mm or 150mm (+/- 3%) x 33 metres
<b>Temperature Range</b>	-40 °C to +80°C
<b>Chemical Resistance</b>	Good
<b>Water Resistance</b>	Good
<b>Interior Use</b>	Excellent
<b>Exterior Use</b>	Pipemark Outdoor recommended
<b>Standards</b>	Layout – BS1710                      Colour – BS4800
<b>Shelf Life</b>	2 years when stored at the recommended temperature 20-25°C
<b>Note</b>	<i>The value given are typical, given in good faith without warranty. No recommendations for specific application or use are given.</i>  <i>The user must satisfy themselves as to the suitability of a particular grade for their own application</i>

ASL00008 Ver 2. Oct 2025.



Albion Systems Limited

**Albion House, 1a Bold Street  
Altrincham, WA14 2ER**

**Tel: 0161 927 2300    Fax: 0161 927 2301    Email: sales@pipemark.co.uk**